

- ✓ Easy installation
- ✓ Self rotating and stainless steel
- ✓ Adjustable and non adjustable versions
- ✓ Protection plate available
- ✓ Maintenance free

Clean vent hoods, trash chutes, pipes, totes, manholes and most containers. This self rotating unit is completely maintenance free. The rotating head spins within the protective cage directing the high pressure spray to your surface. The installation is simple and fast.



(81.522)

* Nozzles not included.

Important:
Do not use unprotected!

TYR *adjustable*

The adjustable arms allow different spray angles. Perfect for horizontal ducts and tanks.

| warm water | | cold water | | ø | IN | Height | Weight |
|------------|----------|------------|----------|-----|---------|--------|--------|
| TYR-2s | TYR-3s | TRR-2s | TRR-3s | | | | |
| Part No. | Part No. | Part No. | Part No. | | | | |
| 81.501 | 81.701 | 85.501 | 85.701 | 75 | G1/4" F | 60 | 0.5 kg |
| 81.502 | 81.702 | 85.502 | 85.702 | 75 | G3/8" F | 60 | 0.5 kg |
| 81.521 | 81.721 | 85.521 | 85.721 | 150 | G1/4" F | 70 | 0.8 kg |
| 81.522 | 81.722 | 85.522 | 85.722 | 150 | G3/8" F | 70 | 0.8 kg |
| 81.551 | 81.751 | 85.551 | 85.751 | 300 | G1/4" F | 70 | 1.1 kg |
| 81.552 | 81.752 | 85.552 | 85.752 | 300 | G3/8" F | 70 | 1.1 kg |
| 81.561 | 81.761 | 85.561 | 85.761 | 400 | G1/4" F | 70 | 1.3 kg |
| 81.562 | 81.762 | 85.562 | 85.762 | 400 | G3/8" F | 70 | 1.3 kg |
| 81.571 | 81.771 | 85.571 | 85.771 | 500 | G1/4" F | 70 | 1.6 kg |
| 81.572 | 81.772 | 85.572 | 85.772 | 500 | G3/8" F | 70 | 1.6 kg |
| 81.581 | 81.781 | 85.581 | 85.781 | 600 | G1/4" F | 70 | 1.8 kg |
| 81.582 | 81.782 | 85.582 | 85.782 | 600 | G3/8" F | 70 | 1.8 kg |



(81.422)

* Nozzles not included.

Important:
Do not use unprotected!

TYR *fixed*

The non adjustable arms with fixed spray angle is perfect for vertical chutes.

| warm water | | cold water | | ø | IN | Height | Weight |
|------------|----------|------------|----------|-----|---------|--------|--------|
| TYR-2f | TYR-3f | TRR-2f | TRR-3f | | | | |
| Part No. | Part No. | Part No. | Part No. | | | | |
| 81.401 | 81.601 | 85.401 | 85.601 | 75 | G1/4" F | 60 | 0.5 kg |
| 81.402 | 81.602 | 85.402 | 85.602 | 75 | G3/8" F | 60 | 0.5 kg |
| 81.421 | 81.621 | 85.421 | 85.621 | 150 | G1/4" F | 70 | 1.0 kg |
| 81.422 | 81.622 | 85.422 | 85.622 | 150 | G3/8" F | 70 | 1.0 kg |
| 81.451 | 81.651 | 85.451 | 85.651 | 300 | G1/4" F | 70 | 1.3 kg |
| 81.452 | 81.652 | 85.452 | 85.652 | 300 | G3/8" F | 70 | 1.3 kg |
| 81.461 | 81.661 | 85.461 | 85.661 | 400 | G1/4" F | 70 | 1.5 kg |
| 81.462 | 81.662 | 85.462 | 85.662 | 400 | G3/8" F | 70 | 1.5 kg |
| 81.471 | 81.671 | 85.471 | 85.671 | 500 | G1/4" F | 70 | 1.6 kg |
| 81.472 | 81.672 | 85.472 | 85.672 | 500 | G3/8" F | 70 | 1.6 kg |
| 81.481 | 81.681 | 85.481 | 85.681 | 600 | G1/4" F | 70 | 1.8 kg |
| 81.482 | 81.682 | 85.482 | 85.682 | 600 | G3/8" F | 70 | 1.8 kg |

TECHNICAL DATA

| | | | |
|--------------------|-----------------------------|-------------------|--|
| Pressure | 275 bar | Nozzles | 2f/2s for 2x 1/8" Nozzles* 3f/3s for 3x 1/8" Nozzles* |
| Temperature | TYR 120°C / TRR 30°C | Throughput | ph 3 - 12 |
| Inlet | see chart | | |
| Body | stainless steel | | |
| RPM | TYR 2000 rpm / TRR 1000 rpm | | |